

MODEL NUMBER / ORDERING KEY

SERIES	SIZE	NOMINAL LUMENS	LED TYPE	COLOR TEMP	REFLECTOR BEAM	REFLECTOR FINISH	REFLECTOR COLOR	FLANGE COLOR	DIMMING
CLS1 LED Cylinder Single Light	08 8" Diameter 10 10" Diameter	10 1000 lumens 20 2000 lumens 30 3000 lumens	PT8 Philips DLM Fortimo, 80CRI	27K 2700 Kelvin 30K 3000 Kelvin 35K 3500 Kelvin 40K 4000 Kelvin	N <sup>1</sup> Narrow M Medium W Wide	RM Semi-specular (Anodized) RD Diffused (Anodized) RS Specular (Anodized) RP Painted	ANODIZED (Blank or CL) Clear CZ Bronze CB Black CK Gold CG Graphite CH Warm Haze CP Pewter CT Wheat CS Straw PAINTED CW Painted White	(Blank or FM) Match reflector color FB Black FW White	(Blank or DUX) Non dimming (120V-277V) DU1 0-10V dimming (120V-277V) DU5 Lutron® Hi-Lume 1% 3 wire dimming (120V-277V) DU6 Lutron® Hi-Lume 1% EcoSystem dimming (120V-277V) D13 Lutron® Hi-Lume 1% 2 wire leading edge dimming (120V) D14 2 wire trailing edge dimming (120V)
	See dimension chart for exact sizes.	Listed lumen output is nominal. Consult factory for max ambient temperature.		<sup>1</sup> Not available on 8".		Contact factory for other anodized and painted colors.	For other voltages and dimming options, consult factory. Consult factory for dimmer compatibility.		

HOUSING COLOR	SUSPENSION	SUSPENSION LENGTH	SUSPENSION COLOR	EMERGENCY	LENS	OTHER
HB Black	KS Stem (Pole)	M006 6" Drop	MB Black	(Blank or EBXX) No emergency battery back-up installed	(Blank or LXX) No lens installed	(Blank or SXX) No option included
HW White	KF Flush Mount	M012 12" Drop	MW White		L01 Frosted lens	
HS Silver	KC Single Cable	M018 18" Drop	MS Silver		L02 Transparent lens	
HZ Bronze	KT Tri Cable	M024 24" Drop	MZ Bronze			
	KA Stem Sloped	M036 36" Drop				
	KX No Hardware	M048 <sup>2</sup> 48" Drop M072 72" Drop M096 <sup>2</sup> 96" Drop MXXX <sup>3</sup> No Length				
For custom colors, consult factory.		<sup>2</sup> Suspension types KC and KT must select from these lengths. <sup>3</sup> Suspension types KF must select this option.				

Product specifications subject to change without notice.  
For the most current spec sheet, visit our website [www.lumenoptix.com](http://www.lumenoptix.com).