

MODEL NUMBER / ORDERING KEY

SERIES	SIZE	NOMINAL LUMENS			LED TYPE/CRI	COLOR TEMPERATURE	DIMMING	MOUNT TYPE	FLANGE
LUZ LED Recessed Grid Panel Luminaire	22 2x2	2x2 2400 lumens	2x4 4000 lumens	1x4 3500 lumens	EA8 > 80CRI	35K 3500 Kelvin	DU1 0-10V dimming (120V-277V) DU5¹ Lutron® 3 wire dimming (120V-277V) DU6 Lutron® EcoSystem dimming (120V-277V) D13¹ 2 wire leading edge dimming (120V) <i>For other voltages and dimming options, consult factory.</i> ¹ Not available with 5000 lumen or greater option.	(Blank or KG) Recessed Grid KS Surface Mount KQ Pendant Quad Cable KR Pendant With Driver In Canopy	(Blank or FW) White Flange FB Black Flange
	24 2x4	40	35			40K 4000 Kelvin			
	14 1x4	40 4000 lumens	75 7500 lumens			50K 5000 Kelvin			

OPTIONS (Pre-installed when specified)	
EMERGENCY LIGHTING	OTHER
(Blank or EBXX) No emergency battery back-up installed EB02 Emergency battery back-up	(Blank or SXX) No option included

Product specifications subject to change without notice.
For the most current spec sheet, visit our website www.lumenoptix.com.