

Downlights Specification Downlight Retrofit

MODEL NUMBER / ORDERING KEY

SERIES	LUMEN	LED TYPE/CRI	COLOR TEMPERATURE	BEAM	FINISH	COLOR	FLANGE	DIMMING			
SDR6S 6" Downlight Small	10 1000 lumens	LA8 Lumileds COB-82CRI	27K 2700 Kelvin	N¹ Narrow	RM Semi-specular (Anodized)	ANODIZED (Blank or CL) Clear	(Blank or FM) Match reflector color	D1X Non dimming (120V)			
SDR6 6.5" Downlight	15 1500 lumens		30K 3000 Kelvin	M² Medium					CZ⁴ Bronze	FB Black	D2X Non dimming (277V)
SDR7 7" Downlight	20 2000 lumens		35K 3500 Kelvin	W Wide					RD Diffused (Anodized)	CB⁴ Black	D11 0-10V dimming (120V)
SDR8 8" Downlight	30 3000 lumens		40K 4000 Kelvin	S³ Wall Wash					RS Specular (Anodized)	CK⁴ Gold	D21 0-10V dimming (277V)
SDR10 10" Downlight	40 4000 lumens		50K 5000 Kelvin						RP Painted	CG⁴ Graphite	D15 Lutron® Hi-Lume 1% 3 wire dimming (120V)
										CH⁴ Warm Haze	D25 Lutron® Hi-Lume 1% 3 wire dimming (277V)
										CP⁴ Pewter	D16 Lutron® Hi-Lume 1% EcoSystem dimming (120V)
										CT⁴ Wheat	D26 Lutron® Hi-Lume 1% EcoSystem dimming (277V)
										CS⁴ Straw	D13 Lutron® Hi-Lume 1% 2 wire leading edge dimming (120V)
										PAINTED CW⁴ Painted White	D14 2 wire trailing edge dimming (120V)
<i>See dimension chart for exact sizes.</i>	<i>Consult factory for max ambient temperature.</i>			¹ Not available on 6". ² Not available on 7". ³ Only available on 6".	<i>Contact factory for other anodized and painted colors.</i>	<i>For custom colors, consult factory.</i>	<i>For other voltages and dimming options, consult factory. Consult factory for dimmer compatibility.</i>				
					⁴ Not EnergyStar certified.						

OPTIONS (PRE-INSTALLED)

EMERGENCY LIGHTING	LENS	OTHER
(Blank or EBXX) No emergency battery back-up installed	(Blank or LXX) No lens installed	(Blank) No option included
EB01 Emergency battery back-up	L01⁴ Frosted lens	
	L02 Transparent lens	
	⁴ Not EnergyStar certified	

VISIT WWW.LUMENOPTIX.COM FOR AVAILABLE ACCESSORIES

GOOF RING	REMODEL RING	STEP DOWN TRANSFORMER
GR Goof Ring	RR Remodel Ring	V2⁶ Step-down transformer (for 347-480V)
GC Goof Ring, custom color or size	RK Rough-in Kit	
		⁶ Must select 277V dimming option.

Product specifications subject to change without notice.
For the most current spec sheet, visit our website www.lumenoptix.com.