

Low-Profile Basket Luminaire

MODEL NUMBER / ORDERING KEY

STE			SA8				
SERIES	SIZE	NOMINAL LUMENS		LED TYPE/CRI	COLOR TEMPERATURE	DIMMING	MOUNT TYPE
STE LED Low-Profile Basket Luminaire	22	<u>2x2</u>	<u>2x4</u>	SA8 > 80CRI	35K 3500 Kelvin	DU1 0-10V dimming (120V-277V)	(Blank or KG) Recessed Grid
	24	38	50		40K 4000 Kelvin		
	2x2	3800 lumens	5000 lumens		50K 5000 Kelvin	DU6 Lutron® EcoSystem dimming (120V-277V)	KS <sup>2</sup> Surface Mount
	2x4					D13 <sup>1</sup> 2 wire leading edge dimming (120V)	KQ <sup>2</sup> Pendant Quad Cable
						For other voltages and dimming options, consult factory.	
						<sup>1</sup> Not available with 5000 lumens or greater option.	<sup>2</sup> Consult factory.

OPTIONS (Pre-installed when specified)		
EMERGENCY LIGHTING	LENS	OTHER
(Blank or EBXX) No emergency battery back-up installed	(Blank or LXX) Standard opal diffused lens	(Blank or SXX) No option included
EB02 Emergency battery back-up	L11 <sup>2</sup> Honeycomb diffused lens cover	
	<sup>2</sup> Consult factory.	

Product specifications subject to change without notice.  
For the most current spec sheet, visit our website [www.lumenoptyx.com](http://www.lumenoptyx.com).