

MODEL NUMBER / ORDERING KEY

See separate spec sheets for detailed information on available options and accessories

STR	2		TA7								
SERIES	FIXTURE LENGTH	NOMINAL LUMENS	LED TYPE/ CRI	COLOR TEMPERATURE	BEAM DISTRIBUTION	INPUT/DIMMING	MOUNTING	CORDSET	SENSOR READY WIRING	EMERGENCY LIGHTING	OTHER
STR STRATOS High Bay Rack Lighter	2 2ft	9 9000 lumens 13 13000 lumens	TA7 High efficienc 70 CRI	40K 4000 Kelvin 50K 5000 Kelvin	A1 ¹ Focus - Medium (0.3 X 1.5 SC) A2 ² Focus - Wide (0.3 X 2.0 SC)	DUX Non dimming (120V-277V) DHX Non dimming (347V-480V) DU1 0-10V dimming (120-277V) DH1 01-10V dimming (347-480V)	KWV 4" Wire 'V' Hook (Pair) KT1 10' Toggle and Cable Set with 18" Y's	CXX No cord C01 6' 18/3 300V cord C02 6' 18/3 600V cord C03 15' 18/3 300V cord C04 15' 18/3 600V cord C05 6' 18/3 cord with Nema 5-15 plug C06 6' 18/3 cord with Nema L7-15 plug C07 15' 18/3 cord with Nema L7-15 plug C13 15' 18/3 cord with Nema 5-15 plug C16 6' 18/3 cord with Nema L8-20 plug C17 15' 18/3 cord with Nema L8-20 plug	(Blank or NXX) No sensor NAS Aisle motion sensor std. temperature NAL Aisle motion sensor low temperature	(Blank or EBXX) No emergency battery back-up installed EB01 ³ Emergency battery back-up	(Blank or SXX) No option include
					¹ Only available with 9000 lumen opt on. ² Only available with 13000 lumen option.	For other dimming options, consult factory.				³ Not available with 347V/480V.	

Product specifications subject to change without notice.
For the most current spec sheet, visit our website www.lumenoptix.com.